



Fujitsu fi-65F
Portable Scanners
FJ3000



Ideal for busy
office
environments!

The compact, lightweight Fujitsu fi-65F Passport Scanner is ideal for busy office and retail environments. Its compact size makes it an ideal counter top scanner for use in the medical, financial, leisure, transportation, education and government sectors or for any user that has the need to instantly capture small format material such as passports, driving licences, identification or insurance cards. It quickly scans important, small documents like passports, IDs, prescriptions, driving licences, customer and medical cards and photographs, and seamlessly integrates with virtually any line of business application (LoB). The fi-65F weighs less than 1kg and has an impressively small footprint of only 145 x 234mm, making it ideally suited for even the smallest desktop, reception, check-in desk or cashier booth. It can even be built into the counter-top. The device features high-speed USB 2.0 connectivity, outstanding performance and easy installation. The scanner can be powered through a second USB port on the computer - it can be used easily even in mobile environments where an AC power supply is unavailable. Main features: Ultra-fast and very compact flatbed scanner for scanning ID cards, passports. 600dpi, USB2, 1 year warranty RTB.

Fujitsu fi-65F

Portable Scanners

fi-65F Specifications	
ADF Scan Area - Max.	148x105 mm
Duplex or Simplex	Simplex
ADF Capacity (pages)	1
Flatbed	Yes
Flatbed Scan Area	105 x 148 mm
Duty Cycle	★★★★★
Colour Modes	B&W, Greyscale, Colour
Scanning Technology	CIS
Interface	USB2
Resolution (dpi, optical)	600
File Formats	Text Searchable PDF, JPEG
Supported OS	WINDOWS 7, Win 8.1, Win 10. Server 2008, 2012, 2016
Software Standards	Image emphasis, simplified DTC, error diffusion, dither, moire removal, auto de-skew, auto-cropping, dropout colour (R, G, B, None)
Imaging Features	Deskewing, auto-crop, blank page removal.
In the Box	PaperStream IP (TWAIN) driver, PaperStream IP (TWAINx64) driver, PaperStream IP (ISIS) driver, PaperStream Capture, Software operation panel
Electrical	Input: 100-240 VAC, 50/60 Hz. Power consumption:
Light Source	LED
Dimensions	145x234x40 mm
PC Configuration	Minimum: 2GB RAM, USB1. Recommended: 4GB RAM, 2 x USB2 ports
Weight	1.5
Operating Environment	5°C to 35°C, 20-80%RH
Warranty	12 months parts & labour warranty