



## Plustek eScan A350 A4 Document Scanners TK2537



The new Plustek eScan A350 is a **true stand-alone network scanner**. It simply connects to your network and can operate independently from a PC. There's no need to run add-on software on any PC.

The A350 network scanner is able to scan to email, cloud (Dropbox, Google Drive, Evernote, Box, etc.), USB, FTP and network folders.

It supports on-board mail authentication. The Plustek A350 can scan to Sharepoint 2008/2010/2013 but not Sharepoint online.

The large colour IPS touchscreen and a clean user interface make the A350 very easy to use. The home user interface can be further customised to suit your business.

This touchscreen also offers a quick way to review and crop targeted images, before delivering the final digitally captured data.

A scanned document can be sent to multiple destinations, for example to a USB drive and to SharePoint.

The A350 features a fast built-in 50 page automatic document feeder, with ultrasonic detection and long life rollers.

Main features: 25 ppm/ 50 ipm speed (even in colour, providing of course your network is fast enough), 50 sheet A4 automatic document feeder (ADF), True Duplex, ultrasonic multi-feed detection, USB2, Ethernet, LED light source, 1 year warranty RTB

Note: If on occasion you have a requirement to use a Twain scanning application, then the A350 can be connected via USB to a PC. You wouldn't normally buy a true network scanner to do that, but it's nice to have this option should the need arise.

ABBYY FineReader Sprint OCR software is included as a bonus. It's installation is not required to scan images.

# Plustek eScan A350

## A4 Document Scanners

---

eScan A350 Specifications	
ADF (Doc. Feeder)	Yes
ADF Scan Area - Max.	216x356 mm
ADF Scan Area - Min.	51 x 51 mm
Duplex or Simplex	True Duplex
ADF Speed (ppm)	25
ADF Capacity (pages)	50
ADF Speed Duplex (ipm)	50
ADF Paper Path	Straight
Paper Weight	40 to 157 g/m <sup>2</sup>
Duty Cycle	★★★★★
Colour Modes	B&W, Greyscale, Colour
Scanning Technology	2 x CIS
Interface	Ethernet, USB2
Resolution (dpi, optical)	600
Light Source	LED
Dimensions	318x170x189 mm
Weight	4.54
Operating Environment	+ 5 °C to +35°C
Warranty	12 months parts & labour warranty